
NEC Versa TXi AC Adapter

Important Information

Congratulations on purchasing the NEC Versa[®] AC adapter! This adapter allows you to run your NEC Versa TXi system on wall outlet (AC) power and to simultaneously recharge the battery or batteries. Use the AC adapter wherever there is an appropriate wall outlet.

NEC Versa AC Adapter



! WARNING Do not attempt to disassemble the AC adapter. It has no user-replaceable or serviceable parts inside. Dangerous voltage in the AC adapter can cause serious personal injury or death. The AC adapter is intended for use with a computer and must meet EN609050 standards.

! CAUTION The AC adapter for the NEC Versa TXi is intended for use in AC power sources within the range of 100-240 volts AC and 50-60 Hz.

Use only the AC adapter for the NEC Versa TXi system. Although other AC adapters may look similar, using them can damage the system.

Connecting the AC Adapter

The AC adapter, when connected, charges the battery (or batteries) whether or not the computer is powered on. Connect the AC adapter as follows:

1. Connect the AC adapter cable to the power port on the left side of your NEC Versa (see the figure on the following page).
2. Plug one end of the AC power cord into the AC adapter and the other end into a properly grounded 120- or 240-volt, 50- or 60-Hz wall outlet (see the figure on the following page).

Note Australia, Europe, and Asia use an AC power cord specific to each country's standards, so it may not resemble the power cord in the figure.

Information in this publication is subject to change without notice. NEC is a registered trademark and Versa is a U.S. registered trademark of NEC Corporation and/or one or more of its subsidiaries. Both are used under license. All other trademarks and registered trademarks are the property of their respective owners. Printed in the U.S.A. 04/2001.

©2001 NEC Computers Inc.

Connecting the AC adapter



A – Power Port
B – AC Adapter

C – Power Cord

⚠ CAUTION Do not cover or place objects on the AC adapter. Keeping the adapter clear of objects lets the adapter cool properly during use.

Specifications

- Input: 100 to 240 Volts (V) AC, 50 or 60 Hz, 1.3 – 0.65 A
- Output: 15.0 V DC, 4A
- Australia, Europe, and Asia use an AC power cord specific to each country's standards.

NEC

NEC Computers Inc.

819-200741-000
04/2001

